

# 2017 MULE PRO-DX

# SPECIFICATIONS

<b>Model:</b>	MULE PRO-DX EPS KAF1000EHF
<b>Engine Type:</b>	Liquid-cooled, In-line 3-cylinder diesel, OHV
<b>Displacement:</b>	993 cm
<b>Bore X Stroke:</b>	74.0 x 77.0 mm
<b>Compression Ratio:</b>	23.5:1
<b>Valve System:</b>	OHV
<b>Fuel System:</b>	In-line injection pump
<b>Combustion Chamber:</b>	Swirl chamber
<b>Starting:</b>	Electric
<b>Transmission:</b>	Dual range (high/low) CVT with reverse
<b>Final Drive:</b>	2WD / 4WD, shaft, Dual-Mode Differential
<b>Frame:</b>	Ladder type, tubular steel
<b>Steering:</b>	Electric Power Steering (EPS)
<b>Suspension - front:</b>	Double wishbone
<b>Suspension - rear:</b>	Double wishbone
<b>Ground Clearance:</b>	265 mm
<b>Wheel Travel - front:</b>	222 mm
<b>Wheel Travel - rear (right, left):</b>	217 mm / 220 mm
<b>Brakes - front:</b>	Dual 212 mm discs with two-piston calipers
<b>Brakes - rear:</b>	Dual 212 mm discs with single-piston caliper
<b>Wheels type - front:</b>	Steel 12 inch
<b>Wheel type - rear:</b>	Steel 12 inch
<b>Tyre front:</b>	26 x 9.00R12 4PR
<b>Tyre rear:</b>	26 x 11.00R12 4PR
<b>L X W X H:</b>	3,385 x 1,625 x 1,965 mm
<b>Wheelbase:</b>	2,345 mm
<b>Minimum Turning radius:</b>	4.8 m
<b>Seat Height:</b>	885 mm
<b>Fuel Capacity:</b>	30 litres
<b>Curb Mass:</b>	834 kg (includes full tank of fuel and all liquids at optimum levels)
<b>Dry Weight:</b>	799 kg
<b>Cargo bed load capacity:</b>	453 kg
<b>Cargo BedL x W x H:</b>	1,375 x 1,355 x 280 mm
<b>Towing Capacity:</b>	907 kg
<b>Seating Capacity:</b>	3
<b>Maximum Permissible Load:</b>	725 kg
<b>Maximum Power:</b>	17.8 kW {24 PS} / 3,600 rpm
<b>Maximum Torque:</b>	52.1 N.m {5.3 kgf.m} / 2,400 rpm
<b>Colour:</b>	Timberline Green
<b>Warranty:</b>	36 months - Terms and Conditions apply - Discuss with a Kawasaki Dealer